



[PRINT SPECS ↓](#)

imagePROGRAF TM-305 MFP T36

Main Unit Specs

Printer Type 5-Colour 36-inch Printer

Number of Nozzles Total: 15,360 | MBK: 5,120 nozzles | C, M, Y, BK: 2,560 nozzles each

Nozzle Pitch 1,200 dpi | Non-firing nozzle detection and compensation

OS Compatibility Windows® 7, 8.1, 10 (32/64bit) | Windows® Server 2008 R2, 2012, 2012 R2, 2016 (64bit) | Macintosh OS X v10.10.5-v10.12x

Standard Interfaces USB 2.0 High-Speed | 10/100/1000 Base-T/TX | Wireless LAN (IEEE 802.11 b/g/n)

Ink Droplet Size 5 picoliter

Ink Capacity 130 ml or 300ml per colour

Colour Set Pigment: Matte Black, Black, Cyan, Magenta, Yellow

Buffer Ram 128 GB (2 GB Physical)

Media Width Cut Sheet - 8- 36 | Roll Feed - 8 - 36

Media Thickness 0.07-0.8mm

Maximum Roll Print Length Roll Feed - 59' (18 meters) |

Maximum Media Roll Diameter 5.9 (150mm)

Borderless Printing Width 8, 10, 12, 14, 16, 17, 20, 24, 36 B4 (10.12/257 mm), A3 (11.69/297 mm), A3+ (12.95/329 mm), A2 (16.54/420 mm), B2 (20.28/515 mm), A1 (23.39/594 mm), B1 (28.66/ 728 mm), A0 (33.11/841 mm)

Paper Feed Method Roll Feed: One Roll, Top-loading, Front Output | Cut Sheet: Top Loading, Front Output

Languages SGRaster, HPGL/2, HP-RTL, JPEG

Noise Level Approx. Operation: 44 dB (A) or less | Standby: 35 dB (A) or less | Acoustic Power: 6.0 Bels or less

Physical Dimensions 42 x 51 x 35

Weight Approx. 134 lbs (roll holder included, no inks, no print heads)

Power Source AC-100-240V (50-60Hz)

Power Consumption Maximum: 69W or less | Standby 3.6W or less | Power Off: 0.3W or less (Compliant with Executive Order)

Operating Environment Temperature: 59°-86° F (15°-30° C) | Relative Humidity: 10-80% (No Condensation)

User-Replaceable Items Print Head (PF-06) | Maintenance Cartridge (MC-31) | Ink Tanks (PFI-120/PFI-320) | Cutter Blade (CT-08)

Software Included TM Unified Printer Driver, Accounting Manager, Apple AirPrint, Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Tool, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist Lite for Windows, Optimized Driver for AutoCAD, Canon PRINT Inkjet Selphy, Easy Photo Print Editor †

Scanner Type Contact Image Sensor (CIS) technology

Scan Accuracy +/- 0.1%

Speed 13 ips monochrome, 6 ips colour (Copy, Standard Mode)

Optical Resolutions 1200dpi (Adjustable from 100 dpi to 2,400 dpi)

Max Resolutions 9600dpi interpolated

Max. Document Size Width: 38 inch document width (36 inch image width) | Length: 315 (JPG or PDF), 598 (TIFF)

Thickness 0.079in (2mm)

Standard Interface USB 3.0 (PC connector compatible with USB 2.0 and USB 3.0 sockets)
