



[PRINT SPECS ↓](#)

imageRUNNER 1435iF

Main Unit

System Type	Digital Multifunction Imaging System
Operation Panel	5-line LCD
Memory	RAM 512 MB; Standard USB Port
Network Interface Connectors	Standard: 1000Base-T, 100Base-TX, 10Base-T; USB 2.0x1 (Host), USB1x1(Host), USB (Device)
Copy/Print Speed (BW)	Letter: Up to 37 ppm; Legal: Up to 25 ppm
Engine Resolution	600 dpi x 600 dpi; 1200 dpi x 600 dpi (Enhanced)
First-Copy-Out Time (Letter)	As fast as 6.9 Seconds
Paper Sources (20 lb. Bond)	Standard: 500-sheet Cassette, 100 sheet Bypass; Optional: 500-sheet Cassette, Maximum: 1,000 Sheets
Output Capacity (20 lb. Bond)	Maximum: 100 Sheets
Output Paper Sizes	Cassette: Letter, Legal; Bypass: Letter, Legal, Statement, Executive, Custom Size (3"x5" to 8 1/2" x 14"), Envelope (C5/DL/COM-10/ Monarch)
Acceptable Paper Weights	Cassette: 17 lb. Bond to 24 lb. Bond (64 to 90 g/m ²); Bypass: 16 lb. Bond to 34 lb. Bond (60 to 120 g/m ²)
Warm-Up Time	From Power On: 20 Seconds or Less; From Sleep Mode: 7.8 Seconds or Less
Power Requirements/ Plug	120-127VAC, 60Hz, 7.8A/NEMA 5-15P

Sleep Mode	2.0 W or less
Dimensions (HxWxD)	18-3/4" x 21-1/2x18" (475.3 mm x 545 mm x 457 mm)
Weight	Approx 52.3 lb. (23.74 kg)
Toner	17,600 images (Estimated Yield @ 6% Coverage)
Max Copy/Print Size (Platen)	8-1.2" x 14" (215.9 mm x 355.6 mm)

Document Feeder

Scan Method	Duplexing Automatic Document Feeder
Acceptable Originals	5-1/2" x 5" to 8-1/2" x 14"
Scan Speed (Letter)	Simplex: Up to 29 ipm (BW)/ 10 ipm (Colour); Duplex: Up to 10 ipm (BW)/ 6 ipm (Colour)
Paper Capacity	Up to 50 Sheets (20 lb. Bond)

PDL Support

Standard	UFR II LT
Optional	PCL 5e/6, and Adobe PS3
Optional	Barcode Printing Kit

Universal Send

Scanning Method	E-mail, USB, File Server (FTP, SMB)
Communication Protocol	File: FTP (TCP/IP), SMB (TCP/IP); Email: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF, PDF (Compact), PDF, (Compact. OCD), PDF (OCR); Optional: Encrypted PDF, Digital Signature PDF

Fax Specifications

Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 Kbps; G3: 14.4 Kbps

Security Specifications

Standard Department ID Management, IPv6, Restricting Features (Restricting New Addresses on Address Book, Allow Fax Driver TX, Restrict Recall, Confirm Entered Fax Numbers, Restrict Sequential Broadcast, Restrict USB Interface), Memory Lock, MAC/IP Address Filtering, SMTP Authentication POP Authentication before SMTP, IEEE802.1x, Authentication Feature for Send Operation (AuSend), Secured Print, SNMP v1/v3, SSL Encrypted Communication, Fax Forwarding, Fax Destination Confirmation, USB Block, TLS Support for E-mail, Fax TX Archive

Optional Encrypted PDF, Device Signature PDF, uniFLOW
