



[PRINT SPECS ↓](#)

Color imageRUNNER ADVANCE C356iF II

Main Unit

Type	Colour Laser Multifunctional
Core Functions	Print, Copy, Scan, Send, Store, Fax
Processor	Canon Dual Custom Processor (Shared)
Control Panel	10.1" TFT LCD WSVGA Colour Flat-panel
Memory	3.0 GB RAM
Hard Disk Drive	250 GB
Interface Connection Network	1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)
Interface Connection Others	USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)
Paper Capacity (LTR, 20 lb. Bond)	Standard: 650 Sheet, Maximum, 2,300 Sheets
Standard Paper Sources (LTR, 20 lb. Bond)	550-sheet Paper Cassette, 100-sheet Stack Bypass
Optional Paper Sources (LTR, 20 lb. Bond)	550-sheet Paper Cassette (CASSETTE MODULE-AE1), 550-sheet Paper Cassette with cabinet (CASSETTE FEEDING UNIT-AJ1), Triple 550-sheet Paper Cassettes (CASSETTE FEEDING UNIT-AK1)
Paper Output Capacity (LTR, 20 lb. Bond)	Standard: 250 Sheets; Maximum: 500 Sheets (with STAPLE FINISHER-Z1)
Finishing Capabilities	Standard: Collate, Group; With External Finisher: Collate, Group, Offset, Staple
Paper Cassette Supported	Thin, Plain, Recycled, Colour, Heavy, Pre-punched, Bond, Envelope

Media Types

Stack Bypass Supported Media Types Thin, Plain, Recycled, Colour, Heavy, Pre-punched, Labels, Bond, Transparency, Envelope

Cassette Module-AE1 Supported Media Types Thin, Plain, Recycled, Colour, Heavy, Pre-punched, Bond

Cassette Feeding Unit-AJ1 Supported Media Types Thin, Plain, Recycled, Colour, Heavy, Pre-punched, Bond, Transparency

Cassette Feeding Unit-AK1 Supported Media Types Thin, Plain, Recycled, Colour, Heavy, Pre-punched, Bond

Paper Cassette Supported Media Sizes Legal, Letter, Executive, Statement, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 7-1/2" to 8-1/2" x 14")

Stack Bypass Supported Media Sizes Legal, Letter, Executive, Statement, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 5-7/8" to 8-1/2" x 14"), Custom Size (3-7/8" x 5-7/8" to 8-1/2" x 14")

Cassette Module-AE1 Supported Media Sizes Legal, Letter, Executive, Statement, Custom Size (3-7/8" x 7-1/2" to 8-1/2" x 14")

Cassette Feeding Unit-AJ1 Supported Media Sizes Legal, Letter, Executive, Statement, Custom Size (3-7/8" x 5-7/8" to 8-1/2" x 14")

Cassette Feeding Unit-AK1 Supported Media Sizes Legal, Letter, Executive, Statement, Custom Size (3-7/8" x 7-1/2" to 8-1/2" x 14")

Supported Media Weights Cassettes: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²); Stack Bypass: 16 lb. Bond to 80 lb. Cover (60 to 220 g/m²); Duplexing: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²)

Print/Copy Speed (BW and Colour) C356iF II: Up to 36 ppm (Letter); Up to 29 ppm (Legal)

Warm-up Time From Power On: 30 Seconds; From Sleep Mode: 10 Seconds; Quick Startup Mode: 4 Seconds (time from device power-on to when copy jobs can be programmed).

Dimensions (W x D x H) Standard (Desktop): 20-1/8" x 25-1/8" x 25-5/8" (511 mm x 639 mm x 651 mm); With Cassette Feeding Unit- AJ1 or AK1: 20-1/8" x 25-1/8" x 41-9/10" (511 mm x 639 mm x 1,064 mm)

Installation Space (W x D) Basic: 33-1/2" x 35-3/4" (852 mm x 908 mm) With Staple Finisher-Z1: 55-3/8" x 35-3/4" (1,407 mm x 908 mm). Includes consumables.

Weight Standard (Desktop): Approx. 108 lb. (49 kg); With Cassette Feeding Unit- AJ1: Approx. 143.3 lb. (65 kg); With Cassette Feeding Unit-AK1: Approx. 149.9 lb. (68 kg)

Print Specifications

Print Resolution (dpi) 1200 x 600

Standard Page Description Languages UFR II, PCL®6, Adobe® PS® 3

Direct Print Available from USB, Advanced Box, Remote UI, and Web Access. PDF print from Web sites is supported.

Supported File Types PDF, TIFF, JPEG, EPS, XPS

PS Fonts: 136 Roman

UFRII/ PS Operating System	Server 2003/Server 2003 R2/Windows Vista*/Server 2008/Windows* 7/Server 2008 R2/Windows 8/Server 2012/ Windows 8.1/Server 2012 R2/Windows 10/MAC OS X (10.6.8 or later)
PCL Operating System	Server 2003/Server 2003 R2/Windows Vista*/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10

Copy Specifications

First-Copy-Out Time (Letter) As fast as 5.1 seconds (BW)/6.9 seconds (Colour)

Copy Resolution (dpi) Reading: 600 x 600; Printing: 600 x 600

Multiple Copies Up to 999 copies

Magnification 25%-400% (1% Increments)

Preset Reductions 25%, 50%, 64%, 73%, 78%

Preset Enlargements 121%, 129%, 200%, 400%

Basic Copy Features Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

Special Copy Features Two-Sided Original, Finishing, Job Build, N on 1, Density Adjustment, Original Type Selection, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Job Done Notice, Copy ID Card, Detect Feeder Multi Sheet Feed

Scan Specifications

Type Single-pass Duplexing Automatic Document Feeder

Document Feeder Paper Capacity 100 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes Document Feeder Supported Media Sizes

Document Feeder Supported Media Weights BW Original: 13 lb. Bond to 34 lb. Cover (50 to 128 g/m²); CL Original: 17 lb. Bond to 34 lb. Cover (64 to 128 g/m²)

Platen Acceptable Originals Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

Pull Scan Color Network ScanGear2 for both Twain and WIA Supported OS: Windows Vista/7/8/8.1/10/ Server 2008/Server 2008 R2/ Server 2012/Server 2012 R2

Scan Resolution (dpi) 600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Scan to Mobile Devices and Cloud-based Services A range of solutions is available to provide scanning to mobile devices and cloud based services depending on your requirements.

Single-sided Scan Speed (Letter) (BW/CL) 50 ipm (300 dpi)/30 ipm (600 dpi) Double-sided

Double-sided Scan Speed (Letter) (BW/CL) 100 ipm (300 dpi)/50 ipm (600 dpi)

Send Specifications

Destination Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax, IP Fax (Optional)

Address Book LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi) 600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Communication Protocol File: FTP, SMB, WebDAV; Email/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format Standard: TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint, Word, Digital Signature (PDF/XPS)); Optional: PDF (Trace & Smooth)

Universal Send Features Original Type Selection, Two-Sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Direct Send, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

Fax Specifications (Optional)

Modem Speed Super G3: 33.6 Kbps; G3: 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement to Legal

Fax Memory Up to 30,000 Pages

Speed Dials Max. 200

Group Dials/Destinations Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup Yes

Fax Features Original Type Selection, Two-Sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

Store Specifications

Mail Box Simple (Number Supported) 100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

Advanced Box

Communication Protocol SMB or WebDAV Supported

Supported Client PC Windows (Windows Vista/7/8/8.1/10)

Concurrent Connections (Max.) SMB: 64; WebCAV: 3 (Active Sessions)

Available Disc Space Approx. 16 GB

Features Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password

Memory Media USB

Security Specifications

Authentication Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in; Optional: uniFLOW

Standard Data Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)

Optional Data IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Standard Network IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

Environmental Specifications

Operating Environment Temperature: 50 to 86 °F; Humidity: 20 to 80 % RH (no condensation)

Power Requirements 120-127V AC 60 Hz, 6.9 A

Plug (Main Unit) NEMA 5-15P

Power Consumption Maximum: Approx. 1.5 kWh; Standby: Approx. 38.9 W; Sleep Mode: Approx. 0.8 W. 0.8W sleep mode not available in all circumstances due to certain settings.

Typical Electricity Consumption (TEC) Rating 1.2 kWh

Standards ENERGY STAR® Certified

Consumables

Toner

GPR-58 Toner

Toner Yield (Estimated @ 5% Coverage)

Black: 23,000 Images; Colour (C,M,Y): 18,000 Images
