



[DOWNLOAD SPECS](#)

## Color imageRUNNER ADVANCE DX C5740i

### Main Unit

#### Type

Colour Laser Multifunctional

#### Core Functions

*Standard: Print, Copy, Scan, Send, Store*  
*Optional: Fax*

#### Processor

1.75GHz Dual Core Processor

#### Control Panel

10.1" TFT LCD WSVGA Colour Flat-panel

#### Memory

4.0 GB RAM

#### Hard Disk Drive

Standard: 250 GB  
 Maximum: 1 TB

## Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)  
Others Standard: USB 2.0 (Host) x1, USB 3.0 x1 (Host), USB 2.0 x1 (Device)  
Optional: Serial Interface, Copy Control Interface

Others

*Standard:* USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

*Optional:* Copy Control Interface

---

## Paper Capacity (LTR, 20 lb. Bond)

*Standard:* 250 Sheets

*Maximum 3,450 Sheets (with External Finisher and Copy Tray)*

---

## Paper Sources (LTR, 20 lb. Bond)

*Standard:* Dual 550-sheet Paper Cassettes, 100-sheet Stack Bypass

*Optional:* Dual 550-Sheet Paper Cassettes (Cassette Feeding Unit-AM1), 2,450-Sheet, High Capacity Paper Cassette (High Capacity Cassette Feeding Unit-A1), 2,700-Sheet Paper Deck (Paper Deck Unit-F1)

---

## Paper Output Capacity (LTR, 20 lb. Bond)

*Standard:* 1,200 Sheets

*Maximum:* 6,350 Sheets

---

## Finishing Capabilities

*Standard:* Collate, Group

*With Options:* Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand

---

## Supported Media Types

*Multi-purpose tray:* Thin, Plain, Recycled, Colour, Heavy, Coated, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope Paper

*Cassettes:* Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope

---

## Supported Media Sizes

Upper Cassette: Letter, Executive, Statement-R, Envelope [No.10 (COM10), DL, ISO-C5], Custom Size (3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")

Lower Cassette: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 7-1/8" to 12" x 18")

Multi-Purpose Tray: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18"), Custom Size/ Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

---

## Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

## Print/Copy Speed (BW and Colour)

Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")

## Warm-up Time

From Power On: Approx. 10 Seconds  
From Sleep Mode: Approx. 10 Seconds  
Quick Startup Mode: Approx. 4 Seconds

## Dimensions (W x D x H)

24-3/8" x 28-1/2" x 36-7/8" (620 x 722 x 937 mm)

## Installation

Basic: 42-5/8" x 45-3/4" (1,083 x 1,162 mm) (Right Cover Open with Multi-purpose tray extended + Cassette Drawers Open)

## Space (W x D)

Fully Configured: 73-1/2" x 45-3/4" (1,866 x 1,162 mm) (Booklet Finisher-Y1 with the extension tray extended + Paper Deck Unit-F1 + Cassette Drawers open)

## Weight

Approx. 315.3 lb (143 kg)

## Print Specifications

## Print Resolution (dpi)

1200 x 1200

## Standard Page Description Languages

UFR II, PCL6, Adobe PS 3

## Supported File Types

PDF, TIFF, JPEG, EPS, XPS

## Types

---

### Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Google Cloud Print, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

---

### Fonts

*PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese), Barcode Fonts*  
*PS fonts: 136 Roman*

---

### Operating System

UFRII/PS: Windows 7/8.1/10/Server2008/ Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X (10.10 or later)  
PCL: Windows 7/8.1/10/Server2008/ Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019  
PPD: Windows 7/8.1/10, Mac OS X(10.9 or later)

---

## Copy Specifications

---

### First-Copy-Out-Time (LTR)

As fast as 4.1 seconds (BW)  
As fast as 6.1 seconds (Colour)

---

### Copy Resolution (dpi)

600 x 600

---

### Multiple Copies

Up to 999

---

### Magnification

25%-400% (1% Increments)

---

### Preset Reduction/Enlargement

25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%, 400%

---

## Scan Specifications

---

### Type

Single-pass Duplexing Automatic Document Feeder

---

## Document Feeder Paper Capacity

Up to 200 Sheets (20 lb. Bond)

---

## Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,  
Custom Size: 2-3/4" x 5-1/2" to 12" x 17"

---

## Document Feeder Supported Media Weights

1-sided scanning: 13.3 lb bond to 81.4 lb cover (50 to 220 gsm)  
2-sided scanning: 13.3 lb bond to 81.4 lb cover (50 to 220 gsm)

---

## Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects

---

## Pull Scan

Colour Network ScanGear2 for both Twain and WIA Supported OS:  
Windows 7/8.1/10 Server 2008/Server 2008 R2/Server 2012/Server  
2012 R2/ Server 2016

---

## Scan Resolution (dpi)

Scan for Copy: 600 x 600  
Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull)  
600 x 600  
Scan for Fax: 600 x 600

---

## Scan to Mobile Devices and Cloud- based Services

*A range of solutions is available to provide scanning to compatible  
mobile devices and certain cloud-based services depending on your  
requirements.*

---

## Scan Speed (Letter) (BW/CL)

Single-sided Scanning: 135/135 (300 dpi), 80/80 (600 dpi)  
Double-sided Scanning: 270/270 (300 dpi), 160/90 (600 dpi)

---

## Send Specifications

---

## Destination

*Standard:* E-mail/Internet FAX (SMTP), SMB 3.0, FTP, WebDAV, Mail Box  
*Optional:* Super 3 FAX, IP Fax

---

## Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

---

## Send Resolution (dpi)

*Push:* Up to 600 x 600 dpi

*Pull:* Up to 600 x 600 dpi

---

## Communication Protocol

*File:* FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV

*Email:* SMTP, POP3

---

## File Format

TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, User Signature, PDF A/1-b, Limited Colour, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

---

## Fax Specifications

---

### Modem Speed

Super G3: 33.6 Kbps  
G3: 14.4 Kbps

---

### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

---

### Sending/Recording Size

Statement-R to 11" x 17"

---

### Fax Memory

Up to 30,000 Pages (2,000 Jobs)

---

### Speed Dials

Max. 200

---

### Group Dials/Destinations

Max. 199 Dials

---

### Sequential Broadcast

Max. 256 Addresses

---

### Memory Backup

Yes

---

## Store Specifications

---

### Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 Jobs Stored)

---

### Advanced Box

*Communication Protocol:* SMB or WebDAV Supported  
*Client PC:* Windows (Windows 8.1/10)

Concurrent Connections (Max.)

*SMB:* 64

*WebDAV:* 3 (Active Sessions)

---

### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD), Approx. 480 GB (With Optional 1 TB HDD)

---

## Security Specifications

---

### Authentication

*Standard:* Universal Login Manager, uniFLOW Online Express (no charge for this solution; however activation is required), User Authentication, Department ID Authentication, Access Management, System, Device and Function Level Log-in  
*Optional:* uniFLOW

---

### Data

*Standard:* Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control (requires UFP v3.9 or greater)

*Optional:* Hard Disk Drive Mirroring, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (requires uniFLOW)

---

### Network

*Standard:* Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication (v1.0/1.1/1.2/1.3), SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

---

### Document

*Standard:* Secure Watermark, Secure Print, Forced Hold Printing, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, User Signature

---

## Environmental Specifications

## Environmental Specifications

---

### Operating Environment

*Temperature: 10 to 30°C*  
*Humidity: 20 to 80% RH (Relative Humidity)*

---

### Power Requirements

110-127V, 60Hz, 10A

---

### Power Consumption

*Maximum: Approx. 1,800 W*  
*Standby: Approx. 65.2 W*  
*Sleep Mode: Approx. 0.8 W*  
*Typical Electricity Consumption (TEC) Rating 0.57 kWh*

---

### Standards

ENERGY STAR® Certified

---

## Consumables

---

### Toner

GPR-55 Toner  
Toner Yield (Estimated @ 5% Coverage)  
Black: 69,000 Images  
Colour (C,M,Y): 60,000 Images

---