



[DOWNLOAD SPECS](#)

## Color imageRUNNER ADVANCE DX C3725i

---

### Main Unit

---

#### Type

Colour Laser Multifunctional

---

#### Core Functions

*Standard:* Print, Copy, Scan, Send, Store  
*Optional:* Fax

---

#### Processor

1.75 GHz Dual Core Processor

---

#### Control Panel

10.1" TFT LCD WSVGA Colour Touch-panel

---

#### Memory

3.0 GB RAM

---

#### Hard Disk Drive

Standard: 250 GB  
Maximum: 1 TB

---

## Interface Connection

### Network

*Standard:* 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)

*Optional:* NFC, Bluetooth Low Energy

### Others

*Standard:* USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

*Optional:* Copy Control Interface

---

## Paper Capacity (LTR, 20 lb. Bond)

*Standard:* 1,200 Sheets

*Maximum:* 2,300 Sheets

---

## Paper Sources (LTR, 20 lb. Bond)

*Standard:* Dual 550-sheet Paper Cassettes, 100-sheet Multipurpose Tray

*Optional:* Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AP1)

---

## Paper Output Capacity (LTR, 20 lb. Bond)

*Standard:* 250 Sheets

## Paper Output Capacity (LTR, 20 lb. Bond)

*Maximum:* 3,450 Sheets (with Staple Finisher-AA1/Booklet Finisher-AA1 and Copy-Tray-J2)

---

## Finishing Capabilities

*Standard:* Collate, Group

*With Finishers:* Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple on Demand

---

## Supported Media Types

*Multi-purpose Tray:* Thin, Plain, Heavy, Recycled, Coated, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Envelope

*Upper Cassette:* Thin, Plain, Heavy, Recycled, Colour, Tracing, Bond, Transparency, Pre-punched, Envelope

*Lower Cassette:* Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Envelope (Envelope Feeder Attachment A is required)

---

## Supported Media Sizes

*Multi-Purpose Tray:* 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Custom Size/Free Size: 3-7/8" x 5-1/2" to 12-5/8" x 18", Envelopes (COM10 No. 10, Monarch, ISO-C5, DL), Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18")

*Upper Cassette:* Letter, Executive, Statement-R, Custom Size (4-1/8" x 5-7/8" to 11-3/4" x 8-1/2"), Envelopes (ISO-C5)

*Lower Cassette:* 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (4-1/8" x 5-7/8" to 12" x 18"), Envelopes (COM10 No. 10, Monarch, DL)

---

## Supported Media Weights

*Cassettes:* 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

*Multi-purpose Tray:* 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)

*Duplexing:* 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

---

## Print/Copy Speed (BW and Colour)

*Letter:* Up to 25 ppm

*Letter-R:* Up to 20 ppm

*Legal:* Up to 15 ppm

*11" x 17":* Up to 15 ppm

---

## Warm-up Time

*From Power On:* Approx. 10 Seconds (Time from device power-on, until copy ready - not print reservation)

*From Sleep Mode:* Approx. 10 Seconds (Time from exiting Sleep mode to when printing is operational)

*Quick Startup Mode:* Approx. 4 Seconds (Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display)

---

## Dimensions (W x D x H)

22-1/4" x 28-1/2" x 34-7/8" (includes Single Pass DADF)

---

## Installation Space (W x D)

*Basic:* Multi-purpose Tray + Cassette Drawers open: 38-1/2" x 44" (With right cover open + Multi-purpose tray extension extended + paper cassette open)

*Fully Configured:* 65" x 44" (Includes Staple Finisher-AA1/Booklet Finisher-AA1 + Copy Tray-J2 extension extended + paper cassette open)

---

## Weight

Approx. 175.5 lb. (includes toner)

---

## Print Specifications

---

## Print Resolution (dpi)

1200 x 1200, 600 x 600

---

## Standard Page Description Languages

UFR II, PCL<sup>®</sup> 6, Adobe<sup>®</sup> PS<sup>®</sup> 3

## Languages

---

### Supported File Types

PDF, TIFF, JPEG, EPS, XPS

---

### Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Google Cloud Print, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

---

### Fonts

*PCL Fonts:* 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese - requires the optional PCL International Font Set-A1), Barcode Fonts (requires the optional Barcode Printer Kit-D1)

*PS Fonts:* 136 Roman

---

### Operating System

*UFR II/PS:* Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, Mac OS X (10.10 or later)

*PCL:* Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019

*PPD:* Windows® 7/8.1/10, Max OS X (10.9 or later)

Note: Other operating systems and environments including AS/400/UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

---

## Copy Specifications

---

**First-Copy-Out-Time (LTR)** As fast as 5.9 seconds (BW)/8.2 seconds (Colour)

---

**Copy Resolution (dpi)** 600 x 600

---

**Multiple Copies** Up to 999

---

**Magnification** 25%-400% (1% Increments)

---

## Preset Reduction/Enlargement

---

25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%, 400%

---

### Scan Specifications

---

#### Type

Single-pass Duplexing Automatic Document Feeder

#### Document Feeder Paper Capacity

Up to 200 Sheets (20 lb. Bond)

#### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 2-3/4" to 12" x 17"

#### Document Feeder Supported Media Weights

BW/Colour Original: 13.3 lb. Bond to 80 lb. Cover (50 to 220 g/m<sup>2</sup>)

#### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects

#### Platen Maximum Scanning Size

Up to 11-3/4" x 17"

#### Pull Scan

Colour Network ScanGear2 for both Twain and WIA  
*Supported OS:* Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

#### Scan Resolution (dpi)

*Scan for Copy:* 600 x 600  
*Scan for Send:* Push (600 x 600), SMB/FTP/WebDAV, Pull (600 x 600)  
*Scan for Fax:* 600 x 600

#### Scan to Mobile Devices and Cloud based

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your

## and Cloud-based Services

requirements.

---

### Scan Speed (LTR)

Single Sided Scanning: BW: 135 ipm (300 dpi), CL: 51 ipm (600 dpi)  
Double Sided Scanning: BW: 270 ipm (300 dpi), CL: 51 ipm (600 dpi)

---

### Send Specifications

---

#### Destination

*Standard:* E-mail/Internet FAX (SMTP), SMB 3.0, FTP, WebDAV, Mail Box  
*Optional:* Super 3 FAX, IP Fax

---

#### Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

---

#### Send Resolution (dpi)

*Push:* Up to 600 x 600 dpi  
*Pull:* Up to 600 x 600 dpi

---

#### Communication Protocol

*File:* FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV  
*Email:* SMTP, POP3

---

#### File Format

TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

---

### Fax Specifications

---

#### Maximum Number of Connection Lines <sup>2</sup>

---

#### Modem Speed

*Super G3:* 33.6 Kbps  
*G3:* 14.4 Kbps

---

#### Compression Method

MH, MR, MMR, JBIG

---

<b>Resolution (dpi)</b>	400 x 400, 200 x 400, 200 x 200, 200 x 100
-------------------------	--

---

<b>Sending/Recording Size</b>	Statement-R to 11" x 17"
-------------------------------	--------------------------

---

<b>Fax Memory</b>	Up to 30,000 Pages (2,000 Jobs)
-------------------	---------------------------------

---

<b>Speed Dials</b>	Max. 200
--------------------	----------

---

<b>Group Dials/Destinations</b>	Max. 199 Dials
---------------------------------	----------------

---

<b>Sequential Broadcast</b>	Max. 256 Addresses
-----------------------------	--------------------

---

<b>Memory Backup</b>	Yes
----------------------	-----

---

### Store Specifications

---

<b>Mail Box Simple (Number Supported)</b>	100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 Jobs Stored)
---	---

---

<b>Advanced Box</b>	<i>Communication Protocol:</i> SMB or WebDAV Supported <i>Client PC:</i> Windows (Windows 8.1/10)
---------------------	--

Concurrent Connections (Max.)  
*SMB:* 64  
*WebDAV:* 3 (Active Sessions)

---

<b>Advanced Box Available Disc Space</b>	Approx. 16 GB (Standard HDD), Approx. 480 GB (With Optional 1 TB HDD)
--	---

---

### Security Specifications

---

<b>Authentication</b>	<i>Standard:</i> Universal Login Manager, uniFLOW Online Express (no charge for this solution; however activation is required), User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
-----------------------	---

Authentication, Access Management, System, Device and Function Level Log in  
*Optional:* uniFLOW

---

## Data

*Standard:* Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control (requires UFP v3.9 or greater)

*Optional:* Hard Disk Drive Mirroring, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (requires uniFLOW)

---

## Network

*Standard:* Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication (v1.0/1.1/1.2/1.3), SNMP, S/MIME, SIEM Integration

---

## Document

*Standard:* Secure Watermark, Secure Print, Forced Hold Printing, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, User Signature

---

## Environmental Specifications

---

### Operating Environment

*Temperature:* 10 to 30°C

*Humidity:* 20 to 80% RH (Relative Humidity)

---

### Power Requirements

110V-127V, 60Hz, 7.5A

---

### Power Consumption

*Maximum:* Approx. 1,500 W

*Standby:* Approx. 47 W [Reference Value (measured one unit)]

*Sleep Mode:* Approx. 0.8 W (not available in all circumstances due to certain settings)

*Typical Electricity Consumption (TEC) Rating:* 0.30 kWh (based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0)

---

### Standards

ENERGY STAR® Certified

---

## Consumables

---

**Toner** GPR-53 Toner [also available for Colour (C, M, Y). Yield (estimated @ 5% coverage) is 8,500]



