

THE POWER OF  
**NEXT**



Device shown with optional accessories.

## SPECIFICATIONS

### Main Unit

<b>Technology/Type</b>	OLED/A3 Colour Multifunction
<b>Core Functions</b>	Standard: Print, Copy, Scan, Send, Store Optional: Fax, Up to 4 lines
<b>Print Speed (BW and CL)</b>	Up to 50 ppm (Letter) Up to 50 ppm (Statement-R) Up to 30 ppm (Letter-R) Up to 25 ppm (11" x 17")
<b>Control Panel</b>	10.1" TFT LCD WSVGA Colour Touch panel
<b>Memory</b>	5.0 GB RAM
<b>Solid-State Drive</b>	Standard: 256 GB Optional: 1 TB
<b>Interface Connections</b>	<b>NETWORK</b> Standard: 1000Base-T/100Base-TX/10Base-T Optional: Wireless LAN (IEEE 802.11a/b/g/n/ac/ax) <b>OTHERS</b> Standard: USB 2.0 (Host) x 1, USB 3.0 (Host) x 1, USB 2.0 (Device) x 1 Optional: Serial Interface, Copy Control Interface
<b>Paper Sources (Letter, 20 lb. Bond)</b>	Standard: Dual 550-sheet Paper Cassettes, 100-sheet Multi-Purpose Tray Optional: 6,350 sheets with High Capacity Cassette Feeding Unit-G1 + Paper Deck Unit-F3
<b>Paper Capacity (Letter, 20 lb. Bond)</b>	Standard: 1,200 Sheets Maximum: 6,350 Sheets
<b>Output Options</b>	1st Copy Tray Kit-C1, Inner 2way Tray-M1 <sup>1</sup> , Copy Tray-T2, Inner Finisher-N1, Staple Finisher-AH1, Booklet Finisher-AH1, Staple Finisher Lite-B1, Inner 2/3 Hole Puncher-D1 <sup>2</sup> , 2/3 Hole Puncher Unit-A1 <sup>3</sup>
<b>Output Capacity (Letter, 20 lb. Bond)</b>	Standard: 250 Sheets Maximum: 3,450 Sheets

<b>Finishing Capabilities</b>	Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand (Capabilities vary depending on the options installed)
<b>Supported Media Types</b>	<b>Upper Cassette:</b> Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope <sup>4</sup>  <b>Lower Cassette:</b> Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope <sup>5</sup>  <b>Multi-Purpose Tray:</b> Thin, Plain, Recycled, Colour, Heavy, Coated, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Envelope
<b>Supported Media Sizes</b>	<b>Upper Cassette:</b> Standard size: Letter, Executive, Statement-R Custom Size: 4-1/8" x 5-7/8" to 11-3/4" x 8-1/2" Envelopes <sup>4</sup> : ISO-C5  <b>Lower Cassette:</b> Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R Custom Size: 4-1/8" x 5-7/8" to 12" x 18" Envelopes <sup>5</sup> : COM10 No.10, Monarch, DL  <b>Multi-Purpose Tray:</b> Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R Custom size: 3-7/8" x 5-1/2" to 12-5/8" x 18" Free Size: 4" x 5-7/8" to 12" x 18" Long sheet <sup>5</sup> : 3-7/8" x 18" to 12-5/8" x 47-1/4" Envelopes: COM 10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 3-7/8" x 3-7/8" to 12-5/8" x 18"

## SPECIFICATIONS CONTINUED

# imageFORCE C3150

<b>Supported Media Weights</b>	Upper Cassette: 14 lb. bond to 140 lb. index (52 to 256 gsm)
	Lower Cassette: 14 lb. bond to 140 lb. index (52 to 256 gsm)
	Multi-Purpose Tray: 14 lb. bond to 110 lb. cover (52 to 300 gsm)
	Duplexing: 14 lb. bond to 80 lb. cover (52 to 220 gsm)
<b>Warm-up Time</b>	Quick Startup Mode: Approx. 4 Seconds <sup>7</sup>
	From Sleep Mode: Approx. 10 Seconds
	From Power On: Approx. 10 Seconds <sup>8</sup>
<b>Dimensions (W x D x H)<sup>9</sup></b>	22-1/4" x 29-3/8" x 35-3/8" (565 x 745 x 897 mm)
<b>Installation Space (W x D)</b>	Basic: 38-1/2" x 44-7/8" (978 x 1,141 mm) (with right door & multi-purpose tray opened + paper cassette opened) Fully Configured: 65" x 44-7/8" (1,651 x 1,141 mm) (with Staple Finisher-AH1/Booklet Finisher-AH1 + Copy Tray-T2 extended + paper cassette open)
<b>Weight</b>	Approx. 200.6 lb. (91 kg) <sup>10</sup>
<b>Print Specifications</b>	
<b>Print Resolution (dpi)</b>	4,800 x 2,400 <sup>11</sup>
<b>Standard Page Description Languages</b>	Standard: UFR II, PCL6/PCL5, Adobe® PostScript® 3 <sup>7</sup>
<b>Direct Print Supported File Types</b>	PDF, EPS <sup>12</sup> , TIFF/JPEG, and XPS
<b>Printing from Mobile and Cloud</b>	A range of software and MEAP-based solutions are available (including AirPrint, Mopria, IPP Everywhere, Canon PRINT, uniFLOW Online, Universal Print and Cloud Connector) to provide printing from mobile devices or internet-connected devices and cloud-based services <sup>13</sup> depending on your requirements. Please contact your sales representative for further information
<b>Operating System Standard Printing</b>	Android/Windows® 10/Windows® 11/Chrome OS /macOS (11.2.2 or later)/iOS (15.2 or later)/iPadOS
<b>Fonts</b>	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT (Japanese, Korean, Simplified and Traditional Chinese) <sup>14</sup> , Barcode fonts <sup>15</sup> PS fonts: 136 Roman
<b>Operating System<sup>16</sup></b>	UFR II: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (10.14 or later) PCL: Windows® 10/11/Server2016/Server2019/Server2022/Server2025 PS: Windows® 10/11/Server2016/Server2019/Server2022/Server2025, macOS (10.14 or later) PPD: Windows® 10/11, macOS (10.15 or later)
<b>Copy Specifications</b>	
<b>First-Copy-Out Time (Letter)</b>	As fast as 4.2 (BW) / 5.5 seconds (Colour)
<b>Copy resolution (dpi)</b>	600 x 600
<b>Multiple Copies</b>	Up to 999 copies
<b>Magnification</b>	Variable zoom: 25% to 400% (1% Increments)
<b>Scan Specifications</b>	
<b>Type</b>	Single-pass Duplexing Automatic Document Feeder (Multi-Sheet Feed Detection is supported)
<b>Document Feeder Paper Capacity</b>	Up to 200 Sheets (20 lb. Bond)
<b>Document Feeder Supported Media Sizes</b>	Document Feeder media size: 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom size: (2-3/4" x 5-1/2" to 12" x 17")

<b>Document Feeder Supported Media Weights</b>	50 to 220 gsm
<b>Platen Scanning Size</b>	Up to 11-3/4" x 17"
<b>Pull Scan Specifications</b>	Colour Network ScanGear2 for both TWAIN and WIA Supported OS: Windows® 10/11/Server 2016/Server 2019/Server 2022/Server 2025
<b>Scan Resolution (dpi)</b>	600 x 600
<b>Scan Method</b>	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online)
<b>Scan Speed (ipm: Letter)</b>	Single-Scanning: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy) Double Sided-Scanning: 270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)
<b>Send Specifications</b>	
<b>Destination</b>	Standard: E-mail/Internet FAX (SMTP <sup>17</sup> ), SMB, FTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax
<b>Address Book</b>	LDAP (2,000)/Local (1,600)/Speed dial (200)
<b>Communication Protocol</b>	File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3
<b>File Format</b>	TIFF (MMR), JPEG, PDF (Compact, Searchable, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
<b>Send Features</b>	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages
<b>Fax Specifications</b>	
<b>Modem Speed</b>	Super G3: 33.6 kbps G3: 14.4 kbps
<b>Compression Method</b>	MH, MR, MMR, JBIG
<b>Resolution (dpi)</b>	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
<b>Sending/Receiving Size</b>	11" x 17", Legal, Letter, Letter-R, Statement-R
<b>FAX Memory</b>	Up to 30,000 pages (2,000 jobs)
<b>Speed Dials</b>	Max. 200
<b>Group Dials/Destinations</b>	Max. 199 dials
<b>Sequential Broadcast</b>	Max. 256 Addresses
<b>Memory Backup</b>	Yes
<b>Store Specifications</b>	
<b>Mail Box (Number Supported)</b>	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 10,000 Pages (2,000 jobs) Stored
<b>Advanced Box</b>	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 10/11 Concurrent Connections (Max.): SMB:64, WebDAV:3
<b>Advanced Box Available Disc Space</b>	Approx. 16 GB (Standard SSD) Approx. 480 GB (With Optional 1 TB SSD)

<b>Security Specifications</b>	
<b>Authentication and Access Control</b>	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online/uniFLOW <sup>18</sup> (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Microsoft Entra ID Authentication (Password Login, Card Login), Two-Factor Authentication at LUI/RUI, Access Management System (Access Control)
<b>Document Security</b>	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print <sup>18</sup> ), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Secure Watermark
<b>Network Security</b>	TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), up to WPA3 (using Wi-Fi), Enabling/Disabling (Network Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send -Virus Concerns for Email Reception
<b>Device Security</b>	Protecting SSD Data [SSD Data Encryption (FIPS140-3), SSD Lock], Standard SSD Initialize, Initialize (NIST 800-88 PURGE LEVEL), Trusted Platform Module (TPM 2.0), Job Log Conceal Function, Protecting MFP Software Integrity: Verify System at Startup (NIST SP800-193: Protection), Checking MFP Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery), Runtime Intrusion Detection: Trellix Embedded Control <sup>19</sup> , HCD-PP Common Criteria Certification (Validation pending)
<b>Device Management and Auditing</b>	Administrator Password, Digital Certificate And Key Management, SAN certificates, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management) <sup>20</sup> , Image Data Logging, Security Policy Setting
<b>Environmental Specifications</b>	
<b>Operating Environment</b>	Temperature: 50 to 86°F Humidity: 20 to 80% RH (Relative Humidity)
<b>Power Requirements</b>	110-127 V, 50/60 Hz, 12A
<b>Power Consumption</b>	Maximum: Approx. 1,800 W Sleep mode: Approx. 0.5 W <sup>21</sup>  Typical Electricity Consumption (TEC) <sup>22</sup> : 0.5 kWh
<b>Environmental Standards</b>	ENERGY STAR <sup>®</sup> Certified
<b>Consumables</b>	
<b>Toner Cartridges</b>	GPR-1007 Toner BK/C/M/Y GPR-1007L Toner C/M/Y

<b>Toner Yield (Estimated @ 5.0% Coverage)</b>	GPR-1007 BK: 36,000 pages GPR-1007 C/M/Y: 19,000 pages GPR-1007L C/M/Y: 8,500 pages
<b>Paper Source Options</b>	
<b>Cassette Feeding Unit-AZ1</b>	Paper Capacity: Dual 550-sheet Paper Cassettes (20 lb. bond) Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead Paper Size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom size: (4-1/8" x 5-7/8" to 12" x 18") Paper Weight: 14 lb. bond to 140 lb. index (52 to 256 gsm)
<b>High Capacity Cassette Feeding Unit-G1</b>	Paper Capacity: Up to 2,450 Sheets Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Pre-punched, Letterhead Paper Size: Letter Paper Weight: 14 lb. bond to 140 lb. index (52 to 256 gsm)
<b>Paper Deck Unit-F3</b>	Paper Capacity: Up to 2,700 Sheets Paper Type: Thin, Plain, Recycled, Colour, Pre-punched, Letterhead Paper Size: Letter Paper Weight: 14 lb. bond to 28 lb. bond (52 to 105 gsm)
<b>Paper Output Options<sup>23</sup></b>	
<b>1<sup>st</sup> Copy Tray Kit-C1</b>	Tray Capacity: 1-Sided Printing: Letter, Statement, Statement-R: Up to 250 sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 100 Sheets 2-Sided Printing: Letter, Statement, Statement-R: Up to 200 sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 100 sheets Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm)
<b>Inner 2way Tray-M1</b>	(Requires 1st Copy Tray Kit-C1) Tray Capacity: Letter, Statement, Statement-R: Up to 100 sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 50 sheets Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm)
<b>Copy Tray Kit-T2</b>	Tray Capacity [with 20 lb. bond (75 gsm)]: Letter, Statement-R: Up to 100 sheets 11" x 17", Legal, Letter-R, Executive: Up to 75 sheets Paper Weight: 14 lb. bond to 80 lb. cover (52 to 220 gsm)
<b>Inner Finisher-N1</b>	Tray Capacity: Upper Tray: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R : Up to 50 sheets Long sheet length of up to 35-1/2": 1 sheet Lower Tray: Letter, Executive, Statement, Statement-R: Up to 500 sheets 11" x 17", Legal, Letter-R: Up to 250 sheets 12" x 18", Envelope: Up to 10 sheets Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm) Staple Position: Corner, Double Staple Capacity: [14 to 24 lb. bond (52 to 90 gsm)] Letter, Executive: Up to 50 sheets Letter-R: Up to 40 sheets 11" x 17", Legal: Up to 30 sheets Eco Staple: 11" x 17", Letter: Up to 10 sheets [14 lb. bond to 17 lb. bond (52 to 64 gsm)] Up to 8 sheets [18 lb. bond to 21 lb. bond (65 to 81.4 gsm)] Up to 6 sheets [22 lb. bond to 28 lb. bond (82 to 105 gsm)] Staple On Demand: Up to 40 sheets [20 lb. bond (75 gsm)]

<b>Staple Finisher-AH1</b>	<p>Tray Capacity:                      Upper Tray: Letter, Executive, Statement, Statement-R: Up to 250 sheets                      12" x 18", 11" x 17", Legal, Letter-R: Up to 125 sheets                      Lower Tray: Letter, Executive, Statement, Statement-R: Up to 3,000 sheets                      12" x 18", 11" x 17", Legal, Letter-R: Up to 1,500 sheets                      Envelopes: Monarch: 30 sheets, COM10 No.10, DL, ISO-C5: Up to 100 sheets                      Long sheet length of up to 47-1/4" (1,200.0 mm): 20 sheet (ejected to the top of the buffer pass unit and the finisher)                      Paper Weight:                      Upper Tray: 14 lb. bond to 140 lb. index (52 to 256 gsm)                      Lower Tray: 14 lb. bond to 110 lb. cover (52 to 300 gsm)                      Staple Position: Corner, Double                      Staple Capacity: [14 to 24 lb. bond (52 to 90 gsm)]                      Letter, Executive: Up to 50 sheets                      Letter-R: Up to 40 sheets                      11" x 17", Legal: Up to 30 sheets                      Eco Staple:                      11" x 17", Letter: Up to 10 sheets [14 lb. bond to 17 lb. bond (52 to 64 gsm)]                      Up to 8 sheets [18 lb. bond to 21 lb. bond (65 to 81.4 gsm)]                      Up to 6 sheets [22 lb. bond to 28 lb. bond (82 to 105 gsm)]                      Staple On Demand: Up to 50 sheets [14 lb. bond to 24 lb. bond (52 to 90 gsm)]</p>
----------------------------	--

<b>Booklet Finisher-AH1</b>	<p>(Includes the above Staple Finisher-AH1 basic staple specifications.)                      Saddle Stitch paper size:                      12" x 18", 11" x 17", Legal, Letter-R                      Saddle Stitch Staple Capacity:                      Up to 20 sheets x Up to 10 sets [14 lb. bond to 21 lb. bond (52 to 81.4 gsm)] [including 1 cover sheet 14 lb. bond to 140 lb. index (52 to 256 gsm)]                      Non Staple Folded Bunch Capacity:                      up to 3 sheets [14 lb. bond to 28 lb. bond (52 to 105 gsm)]</p>
-----------------------------	--

<b>Staple Finisher Lite-B1</b>	<p>Tray Capacity:                      Upper Tray: Letter, Executive, Statement, Statement-R: Up to 250 sheets                      12" x 18", 11" x 17", Legal, Letter-R: Up to 125 sheets                      Lower Tray: Up to 1,500 sheets                      Envelopes: Monarch: Up to 30 sheets, COM10 No.10, DL, ISO-C5: Up to 100 sheets                      Paper Weight:                      Upper Tray: 14 lb. bond to 140 lb. index (52 to 256 gsm)                      Lower Tray: 14 lb. bond to 110 lb. cover (52 to 300 gsm)                      Staple Position: Corner, Double                      Staple Capacity: [14 to 24 lb. bond (52 to 90 gsm)]                      Letter, Executive: Up to 50 sheets                      Letter-R: Up to 40 sheets                      11" x 17", Legal: Up to 30 sheets                      Staple On Demand: Up to 50 sheets [14 lb. bond to 24 lb. bond (52 to 90 gsm)]</p>
--------------------------------	---

<b>Inner 2/3 Hole Puncher-D1</b>	<p>(Requires the Inner Finisher-N1)                      Two or Three Holes                      Acceptable Punch Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm)                      Acceptable Punch Paper Size:                      Two holes: 11" x 17", Legal, Letter, Letter-R, Executive                      Three holes: 11" x 17", Letter, Executive</p>
----------------------------------	---

<b>2/3 Hole Puncher Unit-A1</b>	<p>(Requires either the Staple Finisher-AH1, Staple Finisher Lite-B1, Booklet Finisher-AH1)                      Two or Three Holes                      Acceptable Punch Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm)                      Acceptable Punch Paper Size:                      Two holes: 11" x 17", Legal, Letter, Letter-R, Executive                      Three holes: 11" x 17", Letter, Executive</p>
---------------------------------	---

<sup>1</sup> Requires 1st Copy Tray Kit-C1.  
<sup>2</sup> Requires the Inner Finisher-N1.  
<sup>3</sup> Requires either the Staple Finisher-AH1, Staple Finisher Lite-B1 or Booklet Finisher-AH1.  
<sup>4</sup> Envelope Feeder Attachment Kit B (standard) is required.  
<sup>5</sup> Envelope Feeder Attachment Kit A (standard) is required.  
<sup>6</sup> Long Sheet Feeding Tray-A1 is required and Staple Finisher-AH1 or Booklet Finisher-AH1 is required.  
<sup>7</sup> Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.  
<sup>8</sup> Time from device power-on until copy ready (not print reservation).  
<sup>9</sup> Standard (including 1-Pass DADF).  
<sup>10</sup> Includes consumables.  
<sup>11</sup> Data processing is 4,800 equivalent x 2,400 equivalent.  
<sup>12</sup> EPS can be printed directly only from the Remote User Interface.  
<sup>13</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.  
<sup>14</sup> Optional PCL International Font Set-A1 is required.  
<sup>15</sup> Optional Barcode Printing Kit-D1 is required.  
<sup>16</sup> Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.  
<sup>17</sup> Available OAuth 2.0 authentication method on Microsoft 365 and Google Workspace.  
<sup>18</sup> Requires optional uniFLOW Online/uniFLOW.  
<sup>19</sup> This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.  
<sup>20</sup> Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.  
<sup>21</sup> 0.5 W is not available in all circumstances due to certain settings.  
<sup>22</sup> Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.2.  
<sup>23</sup> Paper capacity may vary with different paper types/sizes.



canon.ca

As an ENERGY STAR® Partner, Canon Canada Inc. has certified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR® and the ENERGY STAR® mark are registered Canadian marks. Canon, imageFORCE and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Trellix and the Trellix logo are trademarks or registered trademarks of Musarubra US LLC or its subsidiaries in Canada and other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Representative for details. Products shown with optional accessories. Subscription to a third-party cloud service required. Subject to third-party cloud service providers terms and conditions. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. Canon Canada does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
 ©2025 Canon Canada Inc. All rights reserved.