

Printer Type 5-Color 36-inch Printer

Total: 15,360
 MBK: 5,120 nozzles
 C, M, Y, BK: 2,560 nozzles each
 1200 dpi
 Non-firing nozzle detection and compensation
 2400×1200dpi (Max)
 Windows® 7, 8.1, 10 (32/64bit)
 Windows® Server 2008 R2, 2012, 2012 R2, 2016 (64bit)
 Macintosh OS X v10.10.5-v10.12x
 USB 2.0 High-Speed
 10/100/1000 Base-T/TX
 Wireless LAN (IEEE 802.11 b/g/n)
 Minimum 5 picoliter
 55 ml per color
 Pigment Ink
 Pigment: Matte Black, Black, Cyan, Magenta, Yellow
 2 GB (Physical)
 Cut Sheet - 8" - 17"
 Roll Feed - 8" - 24"
 0.07-0.8mm

5.9" (150mm)

8" - 24"

Roll Feed: One Roll, Top-loading, Front Output
 Cut Sheet: Top Loading, Front Output
 SGRaster, HPGL/2, HP-RTL, JPEG
 Operation: 42 dB (A)
 Standby: 35 dB (A) or less
 Acoustic Power: 5.8 Bels
 42" x 39" x 34" (H x W x D)
 approx.101 lbs (roll holder included, no inks, no print heads)
 AC 100-240V (50-60Hz)

Maximum: 52W or less
 Standby 3.6W or less
 Power Off: 0.3W or less (Compliant with Executive Order)
 Temperature: 59°-86° F (15°-30° C)
 Relative Humidity: 10-80% (No Condensation)
 Print Head (PF-06)Maintenance Cartridge (MC-31)Ink Tanks (PFI-030)Cutter Blade (CT-08)
 TA Unified Printer Driver, Accounting Manager, Apple AirPrint, Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Tool, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, Optimized Driver for AutoCAD, Canon PRINT Inkjet Selphy, EasyPhoto Print Editor

Number of Nozzles

Nozzle Pitch

Print Resolution (Up to)

OS Compatibility
Standard Interfaces

Ink Droplet Size

Ink Capacity

Ink Droplet Size

Color Set

Buffer Ram

Media Width

Media Thickness

Maximum Media

Roll Diameter

Borderless Printing Width

Paper Feed Method

Languages

Noise Level Approx

Physical Dimensions

Weight

Power Source

Power

Consumption

Operating Environment

User-replaceable items

Software Included